Playing Internet streams with MPlayer for OS/2

by Sjoerd Visser Warpstock 2007 Europe

Subjects

This presentation is about Mplayer for OS/2 What is Mplayer? How to install it? How to use it?

Today (eCS times) OS/2 life is easy... Just subscribe to the OS2VOICE Newsletter.

Mplayer: The Movie Player

[VOICENWS] SW: MPlayer for OS/2 r24878 3.3.5 (based on MPlayer 1.0 RC3)

From: Mark Dodel <feedbackDESPAM@DESPAMos2voice.org>

Date: 31-10-2007 05.30

KO Myung-Hun has released a new version of MPlayer for OS/2 on hobbes. This program is the OS/2 port of MPlayer.

MPlayer is a movie player which runs on many systems (see the documentation). It plays most MPEG/VOB, AVI, Ogg/OGM, VIVO, ASF/WMA/WMV, QT/MOV/MP4, RealMedia, Matroska, NUT, NuppelVideo, FLI, YUV4MPEG, FILM, RoQ, PVA files, supported by many native, XAnim, and Win32 DLL codecs. You can watch VideoCD, SVCD, DVD, 3ivx, DivX 3/4/5 and even WMV movies.. Supports DIVE/WarpOverlay!, DART.

The main MPlayer web site (not for OS/2, just general information) is http://www.mplayerhq.hu

How to install Mplayer for OS/2 (1)

So far I have not been able to get this release to work at all.

If anyone has success I'd love to hear how you did it.



```
Requires kLIBC v0.6.3 ftp://ftp.netlabs.org/pub/gcc/libc-
0_6_3-csd3.wpi
Hobbes:
http://hobbes.nmsu.edu/pub/os2/apps/mmedia/video/players/mplaye
r-dev-svn-r24878-os2-3.3.5.zip
MPlayer for OS/2 source:
http://hobbes.nmsu.edu/pub/new/mplayer-dev-svn-r24878-os2-
3.3.5-src.zip
```

How to install Mplayer for OS/2 (2) (with thanks to Mark Dodel)

(W)Get the files Mark Dodel mentioned.

Install or unpack them by just clicking on it (eCS WPS).

- **libc-0_6_3-csd3.wpi** will launch **Warpin**. Accept the suggested default path (\OS2\DLL).
- mplayer-dev-svn-r24878-os2-3.3.5.zip will lauch the Archive Viewer (AV). AV will suggest the MPlayer path to be .\mplayer-dev-svn-r24878-os2-3.3.5. That's okay.
- **Tip**: copy the mplayer subdirectory to an MMOS2 binary directory on a fast JFS drive (f.i. d:\mmos2\mplayer).
- Then all your **MPlayer CMD batches** (you will get to like them), can refer to your state of the art, latest and greatest MPlayer.
- And you can easily "fall back" when needed.

How to use the Movie Player under OS/2

Mplayer for OS/2 is just an OS/2 application.

- **Mplayer.exe** is basically an OS/2 Command Line Interface (**CLI**) application, that uses the **Simple Direct Layer PM API** for in- and output via the GUI.
- Being a genuine OS/2 application, mplayer.exe can be launched via the WPS just by making a WPS Program object of it.
- But to tweak Mplayer you can use an WPS object of a Mplayer CMD batch. Or better several batches.

And then the "**Drag and drop**" of almost any **mediafile** to your Mplayer WPS objects should work. Under the WPS a file is loaded in the way *you* want to.

• With the massive support of mediafiles of mplayer (more extensions than you would like to know), using initially *.* for the files supported by Mplayer is not a bad idea.

Any Questions?



RTFM: http://www.mplayerhq.hu/design7/info.html

Mplayer can also be used to:

- Play DVD and VCD movies
- Play streaming media (sound, video) from the internet
- Capture streaming media in mpg format
- Show language code and subtitles
- Use Video for Linux (v4l)
- Supports pipes (>, <) and files



CMD to play 10 VOB files in DVD Drive M:

set MPLAYER OPTIONS= -alang nl,en -slang nl,en -dvd-device M: d:\mmos2\mplayer\mplayer dvd://1 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://2 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://3 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://4 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://5 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://6 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://7 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://8 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://9 > NUL 2>&1 d:\mmos2\mplayer\mplayer dvd://10 > NUL 2>&1 exit

How to customize Mplayer_DVD.cmd with some help on short keys

	🗿 mplayer_dvd	
	q Go to the next movie	
mode co80,10	/ Reduce sound volume o Toggle OSD states: none / seek / seek + timer / seek + timer + total	timo
	v Toqqle subtitle visibility.	LTIME .
cls	j Cycle through the available subtitles.	
aecho off	y Step forward in the subtitle list.	
/ ~ / / / / / / / / / / / / / / / / / / /	g Step backward in the subtitle list.	
echo q Go to the next movie	F Toggle displaying "forced subtitles". Ctrl-C or Break to quit	
echo / Reduce sound volume		
echo o Toggie OSD states: no	ne / seek / seek + timer / seek + timer + total time	
echo v Toggle subtitle visibili	ty. ////////////////////////////////////	
echo j Cycle through the avai	lable subtitles.	
echo y Step forward in the su	btitle list.	
echo g Step backward in the	subtitle list.	
echo F Toggle displaying "for	ced subtitles".	
echo Ctrl-C or Break to quit		
set MPLAYER_OPTIONS= y	our options	

How to enable fonts for the Online Screen Display (OSD)

Mplayers Online Screen Display is used for I/O via the PM GUI:

- Input: to enter commands while playing movies.
- Output: to display movie subtitles and its own OSD menu.
- OS/2 ports use Innoteks True type driver by default.
- This OSD has nothing to do with the DVD options menu (:-(

When starting up Mplayer looks for a subfont.ttf in de MPlayer Home directory. This is the under unix "hidden" %HOME%\.mplayer So the easiest way to install an OSD font is:

copy c:\psfonts\arial.ttf c:\home\default\.mplayer\subfont.ttf Here config.sys SET HOME=c:\home\default.

You can set a custom SET HOME= also in your Mplayer batches that contain SET MOPT=[The MPlayer options you don't want to type]

A nice feature of recent gcc libs: softlinks implemented as EA's

	unixos2\COREUTILS_5.93\coreutils_5.9
	▶UP-DIR4 19-07-07 8:47
basename.exe cat.exe	subfont.ttf - Instellingen
chgrp.exe	Type Objectklasse Icon File Men
chmod.exe chown.exe	
chroot.exe	File
cksum.exe comm.exe	
cp.exe csplit.exe	
cut.exe	
date.exe dd.exe	
df.exe	Extended Attributes
l ldir.exe player - Inhoud	Attribute:
Bewerken Beeld (
	GEN
	FLAGS SYMLINK
font Mplayer N	
<u> </u>	SYMLINK (EAT_ASCII, 27 bytes)
er_dvd-m_subfont.ttf	f:\psfonts\arialuni.ttf

With "ln.exe" (link) from coreutils-6.9-os2.zip you can even create "soft" EA symlinks to fonts. Softlinks can be copied too (handy when having many homes and using very large fonts). ln -s f:\psfonts\arialuni.ttf

c:\home\sjoerd\.mplayer\subfont.ttf

ls -ila

9127866760652081970 lrwxrwxrwx 1 0 0 24 2007-07-19 08:53 subfont.ttf -> c:\psfonts\arialuni.ttf

(ls done in c:\home\sjoerd\.mplayer)

Use the "o" key to toggle between OSD modes and the "j" key to find your countries subtitle (if available).



Finding alternative languages and subtitle id's (sid)

Fc/a	FC/2: VIDEO_TS.IFO									(xoø	
View:	P:\TE	ST_DVD	\VIDEC	_TS\VI	DEO_TS	.IFO	\ 0 +-	-en	◆ [⊥] de	• [⊥] fr	CP850	60.92%
s 0 en	ah 0	0 fr	0 it	ů es	0 nl	0 eu					© pl (ല

Open the DVD Information (IFO) file and look for your language code.

Here the file contains as alternative languages en, de, fr, it, es and the subtitle languages (-slang) en, de, fr, it, es, nl, sv, fi, no, da, pt, pl and el. The ID's count from 0.

To play a movie (VOB file) with English language and subtitles: SET MOPT=-alang en -slang nl (or MOPT= -sid 5)

The Versioned Object Base (VOB) files contain the movie, the sound and the subtitles in a streaming MPEG2 format. The IFO file contains metadata.

Tip : if the j-toggle does not find your language use a high -sid 12

To see and listen to embedded video and audio streams you need to have a mediaplayer plugin



Real Player under Odin is old (and dangerous on the internet). WarpVision (partly mplayer based) does not get the streams.

Using internet streams with Mplayer



Being an under Linux developed application, Mplayer is very wel equipped to display internet streams.

So "path/mplayer c:/mpg/movie.avi" will work the same as:

"mplayer mms://domain/../movie.wma"

• if you have a fast enough internet connection.

Some measurements with IP monitor (to monitor the used bandwidth in Kbytes/s) and PM View to measure screen size:

MPEG 1.0 layer III (128kbit/s, 44100 Hz) audio with Z!: 16 kB/s.

•480x360 pixels video: 80 - 120 kB/s.

TMF clips 720x576: 80-230 kB/s.

Some problems users encounter on the web: No Windows Media Player or other ("everyone should have this brand") browser plugin available...

🕘 http://www.bbc.co.uk - BBCWorld Servic 🗙 回 🗊

BBC

Settings

Launch this in standalone player

This clip requires Windows Media Player.

To download or upgrade your Windows Media Player for free, visit the <u>Windows Media download</u> page

Alternatively you can try to <u>play the clip in the</u> <u>standalon</u> player or <u>change your preferences</u>.

http://www.bbc.co.uk/worldservice/meta/tx/nb/live_...





Click here to download plugin.

Transferring data from nl.sitestat.com...

OS/2 and Linux Media Players *may* have the <u>codecs</u> (from <u>compress</u> <u>de</u>compress) or <u>codec</u> <u>analogues</u> to decode (decompress) Windows Media Audio (WMA) or Video (WMV) files to a for their API (Odin, Wine) usable format.

But they are not the Windows Media Player that is available on 90% (= MS OEM market share) of the client desktops. MS oriented servers will notice this. And will ask you first to install *their* plugin (even if you browse without administrator rights).

So your browser will see the "Click here to download the plugin" before it gets the URL of the stream. Then it stops. That's not fair play, as alternative media players have no chance to play anything without the URL of the mms://stream.

The Firefox (and by other Mozilla browsers) used MediaConnectivity (MCP) plugin



When you try to open an URL (seamingly) linking to a media file, but then the WWW server refuses you, because your browser is not equipped with the official plugins, what can you do?

Install the MediaPlayerConnectivity :: Firefox Add-on

It is a java and other webscripting deceiving Mozilla plugin that mimics the behaviour of the Windows browsers. So after having seen the "Click here to download the plugin", MCP will return and will suggest the server that the browser has the required plugin.

It will then analyse the information given by the server to the browser and will show the streaming URLs via the clickable MCP logo in the browser window.

You have to tell the MediaConnectivity plugin when and how to use your preferred OS/2 Media Players. Use: Firefox / Tools / MediaConnectivity / Configure

()		MediaPlaye	rConnectivity 0.8.	3		\bigotimes
Wizard	Media players	渊 Tools	Configuration	Contact	? About	
Check to activate	e the extension fo	or media type ar	nd select the applicat	ion to launch:		
😨 🥏 Real Me	dia 🏼 🌆	G:\OS2BIN\mn	nos2\wvgui\video2.	.exe	Browse	1-
🛛 😰 🏘 Window	s Media 🛛 🐚 🛛	G:\OS2BIN\mn	nos2\MPLAYER\mpla	ayer.exe	Browse	
💽 🥝 QuickTir	ne 🐚	G:\OS2BIN\mn	nos2\MPLAYER\mpla	ayer.exe	Browse	
🖸 🗅 Playlist ((pls/m3u) 💋	G:\OS2BIN\mn	nos2\z\z.exe		Browse	
📑 🖻 MP3/AA	C files 🛛 💋	G:\OS2BIN\mn	nos2\z\z.exe		Browse	
🗓 🤢 OGG/Th	eora 123	G:\OS2BIN\mn	nos2\PM123\pm123	}.exe	Browse	
🔄 🗟 Wave/M	1idi/Au/Aif 🐚	G:\OS2BIN\mn	nos2\MPLAYER\mpla	ayer.exe	Browse	
🔀 🔀 Divx	L 🖣	G:\OS2BIN\mn	nos2\MPLAYER\mpla	ayer.exe	Browse	
📝 🔏 Flash					Browse	
💋 🥖 NullSoft	Video				Browse	
🦳 🐜 Shockw	ave				Browse	-
Restore default	options 🗖 Ex	pert mode	ОК	Cancel	Apply	

I prefer to use OS/2 batches to launch Mplayer: you only need to enter your preferred options once.. The argument %f are the filenames or URLs.

🔇 MediaPlaye	rConnectivity 0.8.3			×
Wizard N	1edia players	ools Configuration Contact About		
Check to activate t	he extension for med	a type and select the application to launch:		
😵 🦻 Real Media]] I:\os2bin\mmos2\WarpVisionGUI\video2.exe	%f	Browse
🌆 🦺 Windows N	1edia 🔽	F:\cmd\mplayer.cmd	%f	Browse
💽 🙋 QuickTime		F:\cmd\mplayer.cmd	%f	Browse
📄 🗟 Wave/Mid	i/Au/Aif 🔽 🔽 🗖	F:\cmd\mplayer.cmd	%f	Browse
🕖 🥖 NullSoft Via	ieo VVV	F:\cmd\mplayer.cmd	%f	Browse
athorware 🥏		F:\cmd\mplayer.cmd	%f	Browse
🛅 🗅 Playlist (pl	s/m3u) <mark>┍┍┍</mark>	I:\os2bin\mmos2\z\z.exe	%f	Browse
📑 🗊 MP3/AAC f	iles PPPP;	I:\os2bin\mmos2\z\z.exe	%f	Browse
💀 💀 OGG/Theo	ra VVV	I:\os2bin\mmos2\PM123\pm123.exe	%f	Browse
📝 🔏 Flash	רשש	I:\os2bin\mmos2\MPLAYER_OS2_TEST\mplayer.exe	%f	Browse
🦐 🦏 Shockwav	e EEE	F:\cmd\mplayer.cmd	%f	Browse
Legend: E:Emb C:Con	ed F:captur textMenu A:Autopl			
Restore default op	itions 🔽 Expert n	ode OK	Cancel	Apply

Some simple Mplayer CMD files

A standard mplayer for the internet

call mode co80,30

set MPLAYER_OPTIONS=-autosync 30

d:\mmos2\mplayer\mplayer %1 %2 %3 %4 %5

A dump_stream1.cmd to capture internet streams in temp:

d:\mmos2\mplayer\mplayer -dumpstream %1 %2 %3 %4 -dumpfile %TEMP%\dump1.mpg

A small and silent cli mplayer:

call mode co25,1

set MPLAYER_OPTIONS= -autosync 30

d:\mmos2\mplayer\mplayer %1 > NUL 2>&1

Mozilla / Tools / MCP / Configuration / Tools tab: here you can enter the options of the "open as" menu when you right click on an by MCP detected stream.

۲			Media	Play	/erConnectivit	y 0.8	.3			×
	Wizard	Media players	X		Configuration		Contact	? About		
ſ	Tools availa	ble in the right	clic menu	over	media links a	and 'b	lack box'			1
	Dump stream	1			F:\cmd\mpla	%f	Browse		Delete	
	Mplayer_os2	_test			F:\cmd\mpla	%f	Browse		Delete	
	MPlayer groo	ıt			F:\cmd\mpla	%f	Browse		Delete	
	MPLAYER-DE	V-SVN-R23385-C	S2-3_3_5		F:\cmd\MPL	%f	Browse		Delete	
	MPLAYER-SV	N20070201-052			F:\cmd\MPL	%f	Browse		Delete	
	Add				ı	ι				

Download Manager

		Browse
•	Always use Firefox dowload manager if possible (use specified download manager only stream, rstp)	for mms://

How to capture a stream using a dumpstream batch



To capture a stream with a batch from the tools menu:

- Rightclick on the black area around the MCP logo.
- Choose Media-PlayerConnectivity
- Choose in the Open with.. (Tools) submenu the batch or command
 Watch it grow in temp

The END



Still any questions?